



DK-1000-S

DK1000-S HAMMER

- ✓ ***SD10 SHANK DESIGN***
- ✓ ***NEW GENERATION***
- ✓ ***SUPERIOR TECHNOLOGY***
- ✓ ***STANDARD BIT DIAMETERS, 9.50"-14.00"***
- ✓ ***DELIVERS MORE ENERGY PER BLOW***
- ✓ ***HARDENED PISTON FOR EXTENDED LIFE***
- ✓ ***INNOVATIVE DESIGN FOR MAXIMUM PERFORMANCE WITH MINIMUM MAINTENANCE***

DRILL KING INTERNATIONAL

820 S. Sixth Avenue ♦ Mansfield, TX 76063 ♦ USA

Main#: 817-539-2500 ♦ Fax#: 682-222-1050


Sales#: 817-539-2501 ♦ Toll Free#: 866-900-2487

sales@drillking.net ♦ www.drillking.net

DrillKing DK-1000-S

INTERNATIONAL

The newest generation of Drill King Hammers means faster penetration, longer life, and less down time due to down hole failures.



No. NOMENCLATURE Qty Part Number

HAMMER ASSEMBLY (SD10)		HADK-T1000-S	
1	WEAR SLEEVE	1	HPDK-T10001-S
2	TOP SUB	1	HPDK-T10002-S
3	TOP SUB O-RING	1	HPDK-T10003-S
4	WEAR WASHER (LOWER)	1	HPDK-T10004-S
5	WEAR WASHER (UPPER)	1	HPDK-T10005-S
6	MAKE UP RING	1	HPDK-T10006-S
7	CHECK VALVE	1	HPDK-T10007-S
8	CHOKE SET	1	HPDK-T10008-S
9	C.V. SPRING	1	HPDK-T10009-S
10	AIR DISTRIBUTOR	1	HPDK-T10010-S
11	AIR DIS. O-RING	1	HPDK-T10011-S
12	CYLINDER	1	HPDK-T10012-S
14	PISTON	1	HPDK-T10014-S
17	PISTON RET. RING	1	HPDK-T10017-S
18	BIT RET. RING	1	HPDK-T10018-S
19	BIT RET. RING O-RING	1	HPDK-T10019-S
20	BEARING	1	HPDK-T10020-S
22	CHUCK	1	HPDK-T10022-S

Drilling Parameters	
Working Pressure	150-250
Application Bit	9.50"-14.00"
Feed Force (lbs.)	3,500-7,000

Air Consumption at Different Working Pressures	
150 psi (scfm)	690
200 psi (scfm)	980
250 psi (scfm)	1290

Dimensions & Weights	
TOP SUB : 6.58" API PIN	
Tool Length (in)	59.6
Outside Dia. (in)	8.86
Piston Diameter (in)	6.85
Stroke (in)	3.90
Weight w/o Bit (lbs)	772
Piston Weight (lbs)	117

Nothing contained in this brochure is intended to extend any warranty or representation for applications expressed or implied, regarding the products described herein. Any such warranties or other terms and conditions of sale of products shall be in accordance with Drill King's standard terms and conditions of sale for such products, which are available upon request.